

Insulated Tools

1000V, VDE certified



You can with

KENNEDY®



We keep operations running

Cromwell was started by one man almost 60 years ago. His ambition was to supply local industries with the tools they needed, when they needed them. Today, Cromwell is a global organisation and we're still delivering vital products to our customers. In 2015 we became part of the WW Grainger Inc family, and the partnership has allowed us to grow internationally.

We supply industries all over the world in categories that include hand tools, cutting tools, air tools and abrasives and many more.

With our six decades of experience as a supplier, we know quite a lot about products. That gives us

a unique insight into what our customers need and the challenges they face while balancing quality and value. So, we've developed our own, exclusive brands that offer customers greater choice at fair prices.

But we offer so much more than just a wide choice of products and great customer service, we add value with expert advice. Our team of time-served engineers help customers to solve production problems, improve their operations and increase profitability.

We're more than a supplier, we're part of your team.

Get in touch

For orders and enquiries, please call **+91 (0) 22 4964 6701**
email **sales@cromwell.co.in** or visit **cromwell.co.in**

Follow us on



Keeping Industry Working™



KENNEDY PROFESSIONAL

Open End Insulated Spanners

Chrome vanadium single ended open jaw spanners. Spanner dimensions conform to **DIN 7446**. Fully insulated to conform to **VDE 0680/201** and **EN 60900:2012** standards for safe electrical applications up to 1000V.

Single End Open Jaw



Size	Overall Length	Order Code KEN-534
6mm	105mm	-2232K
7mm	105mm	-2233K
8mm	105mm	-2234K
9mm	105mm	-2235K
10mm	105mm	-8800K
11mm	115mm	-8810K
12mm	125mm	-8820K
13mm	135mm	-8830K
14mm	145mm	-8840K
15mm	155mm	-8850K
16mm	160mm	-8860K
17mm	160mm	-8870K
18mm	170mm	-8880K
19mm	175mm	-8890K
20mm	185mm	-2236K
21mm	190mm	-8910K
22mm	200mm	-2237K
23mm	210mm	-2238K
24mm	225mm	-8940K
26mm	250mm	-2239K
27mm	250mm	-2240K
28mm	275mm	-2241K
30mm	275mm	-2242K
32mm	290mm	-2243K

KENNEDY PROFESSIONAL

Insulated Single End Ring Spanners



Size	Overall Length	Order Code KEN-534
6mm	140mm	-2260K
7mm	140mm	-2261K
8mm	140mm	-2262K
9mm	140mm	-2263K
10mm	165mm	-9200K
11mm	175mm	-9210K
12mm	185mm	-9220K
13mm	195mm	-9230K
14mm	20mm	-9240K
15mm	205mm	-9250K
16mm	205mm	-9260K
17mm	210mm	-9270K
18mm	220mm	-9280K
19mm	230mm	-9290K
20mm	240mm	-2264K
21mm	250mm	-9310K
22mm	260mm	-9320K
23mm	260mm	-2265K
24mm	260mm	-9340K
26mm	280mm	-2266K
27mm	280mm	-2267K
28mm	280mm	-2268K
30mm	300mm	-2269K
32mm	300mm	-2270K

KENNEDY QUALITY INDUSTRIAL TOOLING

Insulated Ratchet Ring Spanner

- Multi-layer insulated to protect against up to 1000 volts
- Sizing details printed on the body of the tool for easy identification
- Available in a range of sizes to suit all requirements
- IEC 60900



Spanner Size	Overall Length	Order Code KEN-534
10mm	135mm	-2328K
11mm	135mm	-2329K
12mm	140mm	-2330K
13mm	140mm	-2331K
14mm	150mm	-2332K
15mm	150mm	-2333K
16mm	160mm	-2334K
17mm	160mm	-2335K
18mm	180mm	-2336K
19mm	180mm	-2337K

KENNEDY QUALITY INDUSTRIAL TOOLING

1/4" Sq. Dr. Standard Length Insulated 6-Point Socket



- Sizing printed on the body of the socket for easy identification
- Dual layers of dipped insulation to isolate against up to 1000 volts
- Individually tested against high voltages to ensure reliable protection
- IEC 60900



Drive size	Socket size	Order Code KEN-534	Drive size	Socket size	Order Code KEN-534
Metric 	5mm	-2378K	Metric 	10mm	-2383K
	6mm	-2379K		11mm	-2384K
	7mm	-2380K		12mm	-2385K
	8mm	-2381K		13mm	-2386K
	9mm	-2382K		14mm	-2387K

KENNEDY QUALITY INDUSTRIAL TOOLING

3/8" Sq. Dr. Standard Length Insulated Hexagon Socket



- Sizing marked on the socket body for easy identification
- Individually tested against high voltage for reliable safety
- Multi-layer insulation isolates against up to 1000 volts of electricity
- IEC 60900



Drive size	Socket size	Order Code KEN-534	Drive size	Socket size	Order Code KEN-534
Metric 	6mm	-2350K	Metric 	15mm	-2359K
	7mm	-2351K		16mm	-2360K
	8mm	-2352K		17mm	-2361K
	9mm	-2353K		18mm	-2362K
	10mm	-2354K		19mm	-2363K
	11mm	-2355K		20mm	-2364K
	12mm	-2356K		21mm	-2365K
	13mm	-2357K		22mm	-2366K
	14mm	-2358K			

Sockets & Accessories



3/8" Sq. Dr. Deep Length Insulated Hexagon Socket

- Individually tested against high voltage
- Dual layers of dipped insulation isolate against up to 1000 volts
- Sizing printed on the body of the socket for easy identification
- IEC 60900



Drive size	Socket size	Order Code KEN-534	Drive size	Socket size	Order Code KEN-534
Metric 	8mm	-2390K	Metric 	16mm	-2398K
	9mm	-2391K		17mm	-2399K
	10mm	-2392K		18mm	-2400K
	11mm	-2393K		19mm	-2401K
	12mm	-2394K		20mm	-2402K
	13mm	-2395K		21mm	-2403K
	14mm	-2396K		22mm	-2404K
	15mm	-2397K			



3/8" Sq. Dr. Standard Length Insulated In Hex Socket

- Sizing information is printed on the side of the socket for easy identification
- Manufactured from high-quality chrome vanadium steel for a durable product
- Double insulation layers isolate against up to 1000 volts of electricity
- IEC 60900



Drive size	Socket size	Overall Length	Order Code KEN-534
Metric 	4mm	65mm	-2415K
	5mm	65mm	-2416K
	6mm	65mm	-2417K
	8mm	65mm	-2418K
	10mm	65mm	-2419K



3/8" Sq. Dr. Deep Length Insulated In Hex Socket

- Dual layers of insulation dip protect against up to 1000 volts of electricity
- Available in a range of sizes to suit all requirements
- IEC 60900



Drive size	Size	Overall Length	Order Code KEN-534
Metric 	4mm	80mm	-2424K
	5mm	80mm	-2425K
	6mm	80mm	-2426K
	8mm	80mm	-2427K
	10mm	80mm	-2428K



Insulated Reversible Ratchet Spanner

All products are quality tested and fully insulated to 1000V AC. Conforms to VDE 0680/201 (except extension bars) and EN 60900:2012 standards. All 1/2" square drive.



Drive size Weight each Order Code KEN-534

Metric



660g

-7400K



1/2" Sq. Dr. 200mm Insulated T- Handle



Drive size Weight each Order Code KEN-534

Metric



450g

-7420K



1/2" Sq. Dr. 125 & 250mm Insulated Extension Bars



Drive size Description Weight each Order Code KEN-534

Metric



125mm Extension Bar

200g

-7440K

250mm Extension Bar

270g

-7460K



1/2" Sq. Dr. Standard Length Insulated Hexagon Socket



Drive size Size Overall Length Weight each Order Code KEN-534

Metric



8mm

37

60g

-2468K

9mm

37

58g

-2469K

10mm

37

60g

-7500K

11mm

37

63g

-7510K

12mm

37

64g

-7520K

13mm

37

64g

-7530K

14mm

37

67g

-7540K

15mm

37

63g

-7550K

16mm

37

69g

-7560K

17mm

37

74g

-7570K

18mm

37

91g

-7580K

19mm

37

83g

-7590K

20mm

37

101g

-7600K

21mm

37

107g

-7610K

22mm

37

114g

-7620K

23mm

37

118g

-2470K

24mm

37

117g

-7640K

27mm

37

181g

-2472K



1/2" Sq. Dr. Deep Length Insulated Hexagon Socket



- Available in a range of sizes to suit a range of applications
- Individually tested to IEC 60900 insulation standards
- Printed sizing on the socket body allows for easy identification
- DIN 7448



Type	Socket Size	Order Code KEN-534	Type	Socket Size	Order Code KEN-534
Metric 	10mm	-2480K	Metric 	17mm	-2487K
	11mm	-2481K		18mm	-2488K
	12mm	-2482K		19mm	-2489K
	13mm	-2483K		20mm	-2490K
	14mm	-2484K		21mm	-2491K
	15mm	-2485K		22mm	-2492K
	16mm	-2486K		24mm	-2493K



1/2" Sq. Dr. Short Length Insulated In Hex Socket



- Insulated with double layers of safety dip for safety
- Socket type and size marked on the body for easy identification
- Available in a range of sizes to suit various tasks
- IEC 60900



Drive size	Socket Size	Overall Length	Order Code KEN-534
Metric 	4mm	70mm	-2498K
	5mm	70mm	-2499K
	6mm	70mm	-2500K
	8mm	70mm	-2501K
	10mm	70mm	-2502K



1/2" Sq. Dr. Deep Length Insulated In Hex Socket



- Coated with two layers of safety dip insulation for protection against live machinery
- Socket size and type printed on the main body for easy identification
- Available in various sizes to suit many applications
- IEC 60900



Drive size	Socket Size	Overall Length	Order Code KEN-534
Metric 	4mm	80mm	-2507K
	5mm	80mm	-2508K
	6mm	80mm	-2509K
	8mm	80mm	-2510K
	10mm	80mm	-2511K



3/8" Sq. Dr. Standard Length TX-E Insulated Socket



- Multi-layer dipped insulation protects users against up to 1000 volts of electricity
- Size and type printed on the body for easy identification
- IEC 60900



Drive size	Socket Size	Order Code KEN-534
Metric 	E5	-2433K
	E6	-2434K
	E7	-2435K
	E8	-2436K
	E10	-2437K
	E11	-2438K
	E12	-2439K
	E14	-2440K



Insulated Adapters

- Printed size and safety information on the adaptor body for easy identification
- Insulated with multi-layer safety dip to isolate against up to 1000 volts of electricity
- Conveniently adapts square drives to hexagonal drives
- IEC 60900



Total Length	Drive Size	Order Code KEN-534
46mm	3/8 in. to 1/4 in.	-2344K
23mm	1/4 in. to 1/4 in.	-2374K



Total length	Drive Size	Order Code KEN-534
23mm	1/4 in. to 3/8 in.	-2370K



1/4" Sq. Dr. Insulated Extension Bar



- Sizing information printed on the size of the bar for easy identification
- Dipped in two layers of insulation to isolate against up to 1000 volts of electricity
- Available in a range of sizes to suit all requirements
- IEC 60900



Drive size	Overall Length	Order Code KEN-534
Metric 	50mm	-2408K
	75mm	-2409K
	100mm	-2410K
	150mm	-2411K



3/8" Sq. Dr. Insulated Extension Bar

- Sizing information printed on the side of the bar for easy identification
- Available in a range of sizes to suit all requirements
- Double dipped in safety insulation to isolate against up to 1000 volts
- IEC 60900




Drive size	Overall Length	Order Code KEN-534
Metric 	125mm	-2462K
	250mm	-2464K

Torque Wrenches, T- Handles & Ratchet Spanners

KENNEDY 3/8" Sq. Dr. 200mm Insulated T-Handle

- Tool information is printed on the body for easy identification
- Multi-layer insulation isolates against up to 1000 volts of electricity
- IEC 60900



Drive Size	Total length	Order Code KEN-534
Metric 	200mm	-2457K

KENNEDY Insulated Reversible Ratchet Handle

- Forward and reverse gears for convenient working
- Individually tested against high voltage
- Style and size printed on the body for easy identification
- Dual-layer insulation protects against electricity up to 1000 volts
- IEC 60900



Drive Size	Overall Length	Order Code KEN-534
1/4	140mm	-2445K
3/8	200mm	-2446K

KENNEDY Insulated T-Socket Wrench

- Size and standards printed on the tool body for easy identification
- Manufactured from heat-treated, galvanised steel pipe for durability
- Available in a range of sizes to suit all requirements
- IEC 60900



Socket Size	Overall Length	Order Code KEN-534
10mm	200mm	-2282K
11mm	200mm	-2283K
12mm	200mm	-2284K
13mm	200mm	-2285K
14mm	200mm	-2286K
15mm	200mm	-2287K
16mm	200mm	-2288K
17mm	200mm	-2289K
19mm	200mm	-2290K
20mm	200mm	-2291K
21mm	200mm	-2292K
22mm	200mm	-2293K
23mm	200mm	-2294K
24mm	200mm	-2295K
10mm	300mm	-2300K
11mm	300mm	-2301K
12mm	300mm	-2302K
13mm	300mm	-2303K
14mm	300mm	-2304K
15mm	300mm	-2305K
16mm	300mm	-2306K
17mm	300mm	-2307K
19mm	300mm	-2308K
20mm	300mm	-2309K
21mm	300mm	-2310K
22mm	300mm	-2311K
23mm	300mm	-2312K
24mm	300mm	-2313K

KENNEDY Insulated Adjustable Torque Wrench

- Manufactured from high-quality materials
- Insulation dipped for multiple layers of protective insulation
- Individually tested with high-voltage for reliable safety
- IEC 60900



Drive Size	Overall Length	Torque Range	Accuracy	Order Code KEN-534
1/4	370mm	5 to 25 Nm	+/-4	-2450K
3/8	205mm	5 to 25 Nm	+/-4	-2452K
3/8	370mm	5 to 50 Nm	+/-4	-2454K
1/2	460mm	5 to 50 Nm	+/-4	-2516K
1/2	205mm	20 to 100 Nm	+/-4	-2518K

Roller Cabinets & Tool Chests

See our range



Scan the QR code



+ + + + + + + + + + + + + + + +
+ + + + + + + + + + + + + + + +



Mains Testers

With heavy duty one-piece moulded insulation sheaths covering both blade and transparent plastic handle for extra protection and safety.

Will detect 'live' electricity supply.

Suitable for AC to 125 - 250V. 3mm wide tip.

Conforms to **DIN VDE 0680 part 6:1977-04**.



| Blade Length | Cap Type | Weight per 12 | Order Code
KEN-515 |
|--------------|----------|---------------|------------------------------|
| 150mm | Plastic | 210g | -0500K |
| 190mm | Plastic | 400g | -0550K |



Electricians Screwdrivers, Phillips Tip

Crosspoint

- Blade lengths: 75-100mm
- Blade sizes: No.0, No.1 and No.2
- Fully insulated
- VDE tested up to 1000VAC or 1500V DC
- High grip handles
- Magnetized tips
- Conform with **DIN 7438** and **DIN EN 60900**



CROSS
POINT



| Tip Size | Blade Length | Order Code
KEN-572 |
|----------|--------------|------------------------------|
| PH0 | 77mm | -5820K |
| PH1 | 100mm | -5830K |
| PH2 | 100mm | -5840K |



Electrician's VDE Screwdrivers, Parallel Tip

- Magnetised tips allow you to effectively hold fasteners in place to apply torque accurately
- Available in a range of sizes to suit your needs
- High grip handles ensure maximum control and comfort when using
- All products are VDE tested up to 1000V AC or 1500V DC to ensure your safety
- **DIN 7438**
- **DIN EN 60900**



PARALLEL



| Tip Size | Blade Length | Order Code
KEN-572 |
|----------|--------------|------------------------------|
| 2.5mm | 85mm | -5760K |
| 4.0mm | 100mm | -5780K |
| 5.5mm | 125mm | -5790K |
| 6.5mm | 150mm | -5800K |

Screwdrivers & Testers



1000V Dual Grip VDE Screwdrivers



A fully insulated VDE screwdriver tested up to 1000V.

Professional high grip handles, magnetic tips, chrome vanadium steel blades.



CROSSPOINT



| Tip Size | Blade Length | Order Code
KEN-572 |
|----------|--------------|------------------------------|
| No.0 | 60mm | -7900K |
| No.1 | 80mm | -7910K |
| No.2 | 100mm | -7920K |

PARALLEL TIP



| Tip Size | Blade Length | Order Code
KEN-572 |
|----------|--------------|------------------------------|
| 2.5mm | 75mm | -7940K |
| 4.0mm | 100mm | -7950K |
| 5.5mm | 125mm | -7960K |
| 6.5mm | 150mm | -7970K |



PARALLEL



CROSS
POINT

Set Contents

(mm):
2x5 x 75,
4.0 x 100,
5.5 x 125,
6.5 x 150mm.

No.0 x 60,
No.1 x 80,
No.2 x 100mm.



7
PIECES

Order Code
KEN-572

-8000K



Electrician's VDE Square Section Handle Screwdriver

Volt-tested to ensure safety on or near electrical equipment up to 1000V AC or 1500V DC. Insulated blades with magnetic tips.

Conform with **DIN 7438** and **DIN EN 60900**



CROSS
POINT



PARALLEL

Set Contents

(mm):
No. 0 x 75mm
No. 1 x 100mm
No. 2 x 100mm

2.5 x 80mm
4.0 x 100mm
5.5 x 125mm
6.5 x 150mm



7
PIECES

Order Code
KEN-572

-5900K



Insulated Interchangeable Screwdriver Set



Ergonomic insulated full size handle, swivel cap and eight interchangeable drivers supplied in a compact protective pouch with belt loop. 2-in-1 design, use the detachable swivel cap for fast (low torque) driving, or use the full size detachable ergonomic handle for higher torque fastening. Safe up to 1000V AC/1500V DC.



PARALLEL



CROSS
POINT

10-Piece Set Contents

(mm):
0.4 x 2.5 x 100mm,
0.5 x 3.0 x 100mm,
0.8 x 4.0 x 100mm,
1.0 x 5.5 x 100mm and
1.2x 6.5 x 100mm.

No.0 x 100mm,
No.1 x 100mm and
No.2 x 100mm.

10
PIECES



Order Code
KEN-572

-5870K



**You can with
Kennedy.**

Quality tools
by **Cromwell**

**With Kennedy tools in your hands,
you can build more. You can build
a reputation.**

Throughout your working life, Kennedy is working to support you – with the tools you need to do the best job you can. We're there when you start your career. We're with you as you build your professional reputation. We're here to help you achieve your full potential in your industry. The work starts today.

KENNEDY®

Pliers



Insulated Combination Pliers, 1000V

- Chrome-plated jaws for durability
- Induction-hardened cutting edges provide reliable performance
- Phthalate-free manufacture avoids the handling of harmful chemicals
- EN 6900
- IEC 60900



Multilayer Insulated



Comfort Grip



Snipe Pliers



Ergonomic Grip



| Overall Length | Features | Order Code
KEN-534 |
|----------------|----------------------|-----------------------|
| 160mm | Multilayer insulated | -2123K |
| 180mm | Multilayer insulated | -2105K |
| 210mm | Multilayer insulated | -2110K |
| 180mm | Ergonomic Grip | -2139K |
| 180mm | Comfort Grip | -2130K |
| 205mm | Comfort Grip | -2133K |
| 210mm | Comfort Grip | -2136K |
| 210mm | Chrome Plated Jaws | -2142K |



Insulated Power Side Cutters

- Sizing printed on the handles for easy identification
- Hardened cutting edges (to 63 HRC) for powerful cutting action
- Safety layer dipped handles isolate against up to 1000 volts of electricity
- IEC 60900



| Overall Length | Capacity | Order Code
KEN-534 |
|----------------|----------|-----------------------|
| 200mm | 2.5mm | -2339K |



Insulated Flat Nose Pliers

- Serrated jaws provide strong gripping action
- Multi-layer insulation protects against up to 1000 volts of electricity
- Chrome-plated tool steel ensures a strong and durable product
- IEC 60900



| Overall length | Order Code
KEN-534 |
|----------------|-----------------------|
| 160mm | -2531K |



Pro-Torq Insulated Long Nose Pliers

Manufactured from specially selected steels. The dual material grip handle design allows the user to apply the greatest force with the minimum amount of effort. Manufactured with a polypropylene core for strength and durability with a soft thermoplastic outer for non-slip comfort grip. Especially suitable for production line environments where repetitive work is undertaken. Double polished head and joint. Induction hardened cutting edges with serrated jaws for gripping nuts.

VDC/IEC 900
DIN EN 60900



DUAL MATERIAL HANDLES



| Overall Length | Jaw Length | Order Code
KEN-558 |
|----------------|------------|-----------------------|
| 160mm | 60mm | -5020K |
| 205mm | 85mm | -5040K |



Pro-Torq Insulated Diagonal Cutting Nippers

Insulated Diagonal Cutting Nippers. Especially suitable for production line environments where repetitive work is undertaken. Double polished head and joint with induction hardened cutting edges.

VDC/IEC 900
DIN EN 60900



DUAL MATERIAL HANDLES



| Overall Length | Jaw Length | Jaw Width | Order Code
KEN-558 |
|----------------|------------|-----------|-----------------------|
| 160mm | 21mm | 21mm | -5100K |
| 180mm | 20mm | 28mm | -5120K |

KENNEDY PROFESSIONAL Pro-Torq Insulated Combination Pliers

Manufactured from specially selected steels. The dual material grip handle design allows the user to apply the greatest force with the minimum amount of effort. Manufactured with a polypropylene core for strength and durability with a soft thermoplastic outer for non-slip comfort grip. Double polished head and joint. For gripping nuts.



VDC/IEC 900
DIN EN 60900



1000VAC

| Overall Length | Jaw Length | Jaw Width | Order Code
KEN-558 |
|----------------|------------|-----------|-----------------------|
| 160mm | 36mm | 26mm | -5140K |
| 180mm | 39mm | 26mm | -5160K |
| 200mm | 42mm | 29mm | -5180K |

KENNEDY QUALITY INDUSTRIAL TOOLING Pro-Torq Insulated End Wire Strippers

Especially suitable for production line environments where repetitive work is undertaken. Double polished head and joint with induction hardened cutting edges.

VDC/IEC 900
DIN EN 60900



1000VAC

| Overall Length | Jaw Length | Jaw Depth | Wire Size | Order Code
KEN-558 |
|----------------|------------|-----------|-----------|-----------------------|
| 160mm | 38.5mm | 16.6mm | 6mm | -5200K |

KENNEDY QUALITY INDUSTRIAL TOOLING Pro-Torq Insulated Plier Set

Double polished head and joint with induction hardened cutting edges. VDC/IEC 900 DIN EN 60900

3 Piece Set Contents:

Nippers 160mm (6³/₈"),
Long nose 160mm (6³/₈"),
Combination 160mm (6³/₈").



3
PIECES

Order Code
KEN-558

-6980K

KENNEDY PROFESSIONAL 1000V Dual Grip Screwdriver & Plier Set

10 Piece Set

Fully insulated professional high grip dual material handles that are VDE tested up to 1000V. Screwdrivers have magnetic tips, chrome vanadium steel blades and a hanging hole.

Contents:

Screwdrivers:

Crosspoint:

No.0 x 60mm,
No.1 x 80mm,
No.2 x 100mm.



CROSS
POINT

Parallel:

2.5 x 75mm,
4.0 x 100mm,
5.5 x 125mm,
6.5 x 150mm.



PARALLEL

Pliers:

- 6³/₈" Pro-Torq snipe nose pliers,
- 6¹/₄" Pro-Torq grip nipper pliers,
- 6¹/₂" Pro-Torq engineering combination pliers.

10
PIECES



Weight
each

1.4kg

Order Code
KEN-595

-1600K

KENNEDY PROFESSIONAL 16 Piece Electrician's VDE Tool Bag & Kit

Heavy duty tear-resistant tool bag with Hook-n-Loop fastening flap. Double webbed shoulder strap fixed with metal release clasps. Two removable tool boards inside which have a unique tool storage securing system built in. All tools are VDE approved.

Contents:

- Electrician's tool bag (320 x 340 x 125mm).
- 150mm euro tester will detect 'live' electricity supply. Suitable for AC to 125 - 250V, 3mm wide tip. Conform to VDE 0630 Part 4.
- 145mm (5³/₄") Pro-Torq grip diagonal nippers, 1000V insulated.
- 160mm (6³/₈") Pro-Torq snipe nose pliers, 1000V insulated.
- 165mm (6¹/₂") Pro-Torq engineer's combination pliers, 1000V insulated.
- 170mm (6³/₄") Pro-Torq wire strippers, 1000V insulated.
- 7 piece VDE dual grip screwdriver set: No.0 x 60, No.1 x 80 and No.2 x 100mm, 2.5 x 75, 4.0 x 100, 5.5 x 125 and 6.5 x 150mm.
- 180mm (7") insulated cable knife, curved blade.
- 2x small parts storage boxes.



16
PIECES

Width
(mm)

320

Depth
(mm)

125

Height
(mm)

340

Order Code
KEN-595

-3400K

Adjustable Wrenches, Cable Cutters & Hexagonal Keys

KENNEDY PROFESSIONAL Insulated Water Pump/Box Joint Pliers

Hardened chromed steel jaws. Sliding pivot joint allows the widest range of jaw openings. Serrated jaws for gripping flat and round parts. The handles cannot be closed together, preventing trapped fingers.

Fully insulated, conforms to **EN 60900:2012** standards for safe electrical applications up to 1000V.



| Overall Length | Weight each | Order Code KEN-534 |
|----------------|-------------|--------------------|
| 240mm | 55g | -4860K |

KENNEDY PROFESSIONAL Insulated Cable Cutters

Manufactured from drop forged high carbon steel with induction hardened blades. Fully insulated to conform with **VDE 0680/201** and **EN 60900:2012** standards for safe electrical applications up to 1000V.



| Overall Length | Capacity | Weight each | Order Code KEN-534 |
|----------------|----------|-------------|--------------------|
| 240mm | 22mm | 398g | -4960K |

KENNEDY PROFESSIONAL Insulated Ratcheting Cable Cutter

For copper and aluminium cables up to 32mm diameter. Lightweight steel handles with insulated vinyl hand grips. Fixed and moving blade made from high grade alloy steel. Quality tested **EN 60900:2012** and insulated to 1000V AC.



| Overall Length | Weight each | Order Code KEN-534 |
|----------------|-------------|--------------------|
| 250mm (10") | 678g | -5000K |

KENNEDY PROFESSIONAL Insulated Hexagon Key

- Multi-layer insulation protects users from up to 1000 volts of electricity
- Key size and type is printed on the handle for easy identification
- Available in a wide range of sizes to suit all requirements
- DIN 911L



| Tip Size | Long Arm Length | Order Code KEN-534 |
|----------|-----------------|--------------------|
| 3mm | 130mm | -2185K |
| 4mm | 140mm | -2186K |
| 5mm | 160mm | -2187K |
| 6mm | 180mm | -2188K |
| 8mm | 200mm | -2189K |
| 10mm | 226mm | -2190K |
| 12mm | 250mm | -2191K |

KENNEDY PROFESSIONAL Insulated Hexagon Key

- Multi-layer insulation protects users from up to 1000 volts of electricity
- Key size and type is printed on the handle for easy identification
- Available in a wide range of sizes to suit all requirements
- IEC 60900



| Tip Size | Long Arm Length | Order Code KEN-534 |
|----------|-----------------|--------------------|
| 3mm | 65 | -2195K |
| 4mm | 70 | -2196K |
| 5mm | 80 | -2197K |
| 6mm | 90 | -2198K |
| 8mm | 100 | -2199K |
| 10mm | 115 | -2200K |
| 12mm | 130 | -2201K |

KENNEDY PROFESSIONAL T-Handle Wrench for Hexagonal Screws

- Size and safety information printed on the side for easy identification
- Individually tested for safety
- Reliable heavy-duty handle for excellent torque delivery
- IEC 60900



| Tip Size | Long Arm Length | Order Code KEN-534 |
|----------|-----------------|--------------------|
| 3mm | 150 | -2207K |
| 4mm | 150 | -2208K |
| 5mm | 150 | -2209K |
| 6mm | 150 | -2210K |
| 8mm | 150 | -2211K |
| 3mm | 250 | -2212K |
| 4mm | 250 | -2213K |
| 5mm | 250 | -2214K |
| 6mm | 250 | -2215K |
| 8mm | 250 | -2216K |

KENNEDY PROFESSIONAL Insulated Adjustable Wrenches

Manufactured from chrome vanadium steel with hardened parallel opening jaws that are ground and polished, laser etched with metric graduations for rapid repeatable reference setting. Knurled adjusting screw ensures smooth adjustment. Fully insulated, conforms to **EN 60900:2012** standards for safe electrical applications up to 1000V.



| Overall Length | Capacity | Weight each | Order Code KEN-534 |
|----------------|----------|-------------|--------------------|
| 150mm | 26mm | - | -2320K |
| 200mm | 26mm | 336g | -6080K |
| 250mm | 35mm | 551g | -6100K |
| 300mm | 35mm | 870g | -6120K |

Hammers, Knives & Hacksaws



Insulated Cable Cutters

- Double cutting edge provides squeeze-free cutting action
- Insulated handles protect against up to 1000 volts of electricity
- Comfortable handle grip for strain-free use
- IEC 60900



| Maximum Cutting Capacity | Overall Length | Order Code |
|--------------------------|----------------|-------------------|
| 10mm | 160mm | KEN-534
-2522K |



Insulated Cable Knives

Fully insulated to conform to **VDE 0680/201** and **EN 60900:2012** standards for safe electrical applications up to 1000V.

Curved Blade: Steel hook blade for splitting flat and ribbon cables along its length.



Straight Blade: Fixed straight blade and protection cap.
Blade length: 45mm.



| Overall Length | Type | Weight each | Order Code |
|----------------|----------------|-------------|-------------------|
| 180mm | Curved Blade | 65g | KEN-534
-3480K |
| 180mm | Straight Blade | 65g | -3500K |



Insulated Dismantling Cable Knife

Insulated dismantling cable knife complete with protection cap. Quality tested to 1000V AC. Comfortable handle, fixed sickle shaped blade for cutting sector cables. Conforms to **VDE 0680/201** and **EN 60900:2012** standards.

Blade length: 45mm.



| Overall Length | Weight each | Order Code |
|----------------|-------------|-------------------|
| 180mm | 70g | KEN-534
-3540K |



Insulated Plastic Hammer

- Multiple layers of insulation protects users against up to 1000 volts of electricity
- Insets are replaceable for a long service life
- Safe, recoil-free design
- IEC 60900



| Head Diameter | Length | Order Code |
|---------------|--------|-------------------|
| 25mm | 310mm | KEN-534
-2526K |
| 35mm | 320mm | -2528K |



Insulated Junior Hacksaw

Tested and insulated to 1000V AC and 1500V DC for live line working. All insulation is moulded in one piece, uses conventional junior hacksaw blades. **EN 60900:2012**.



| Overall Length | Weight each | Order Code |
|----------------|-------------|-------------------|
| 150mm (6") | 264g | KEN-534
-0600K |



Insulated Hacksaw

Die cast frame with 'D' style handle for user comfort and control. Wing nut blade tensioning. Supplied complete with 300mm 24tpi blade. Fully insulated, conforms to **EN 60900:2012** standards for safe electrical applications up to 1000V.



| Overall Length | Weight each | Order Code |
|----------------|-------------|-------------------|
| 400mm | 619g | KEN-534
-0800K |



Insulated Tweezers

Straight/bent pattern tweezers with serrated gripping surfaces, quality tested and insulated to 1000V AC. Conforms to **EN 60900:2012** standards. **Exposed blade length:** 15mm.

Straight Pattern



Bent Pattern



| Overall Length | Type | Weight each | Order Code |
|----------------|----------|-------------|-------------------|
| 145mm | Straight | 40g | KEN-534
-1120K |
| 145mm | Curved | 40g | -1140K |



Insulated Centre Cross Key

- Multi-layer insulated to isolate against up to 1000 volts of electricity
- Prevents the possibility of electrical contact
- IEC 60900



| Drive Size | Order Code |
|---------------|-------------------|
| 10/13/14/17mm | KEN-534
-2275K |
| 13/14/17/19mm | -2277K |

Spanners & Sockets Sets



Insulated Ratchet Ring
Spanner Set

- Sturdy tool case inlay keeps tools secure when on the move
- Sizing information printed on the spanner bodies for easy identification
- Multi-layer insulation isolates against up to 1000 volts of electricity

Contents

- 6 x insulated ratchet spanners (10mm, 11mm, 12mm, 13mm, 14mm, 17mm)
- IEC 60900



| Number of pieces | Overall Length | Order Code |
|------------------|----------------|--------------------------|
| 6 | 140mm | KEN-534
-2324K |



Insulated VDE
Reversible Ratchet Set

- Multi-layer insulation on each item delivers protection against up to 1000 volts of electricity
- Storage case features a two-colour inlay to keep tools secure when on the move
- IEC 60900



Contents (9 Pieces)

- 1 x reversible ratchet tool
- 1 x extension bar
- 7 x sockets (10mm, 11mm, 12mm, 13mm, 14mm, 17mm, 19mm)
- 1 x plastic case with inlay

(For 9 pieces only)



Contents (18 Pieces)

- 1 x 200mm T-handle
- 2 x extension bars (125mm, 250mm)
- 11 x sockets (10mm, 11mm, 12mm, 13mm, 14mm, 17mm, 19mm, 22mm, 24mm, 27mm, 32mm)
- 3 x hex sockets (5mm, 6mm, 8mm)
- 1 x 260mm reversible ratchet



9 Pieces



18 Pieces

| Number of pieces | Order Code |
|------------------|--------------------------|
| 9 | KEN-534
-2248K |
| 18 | -2249K |



Insulated Reversible
Ratchet Safety Tool Set

- Dual-layer insulation protects against up to 1000 volts of electricity
- Sturdy plastic case with insert keeps tools secure when on the move
- IEC 60900



Contents (14 Pieces)

- 1 x 200mm reverse ratchet
- 1 x 200mm t-handle
- 2 x extension bars (125mm, 250mm)
- 7 x sockets (8mm, 10mm, 11mm, 13mm, 14mm, 17mm, 19mm)
- 3 x hex sockets (4mm, 5mm, 6mm)

Contents (18 Pieces)

- 1 x 200mm t-handle
- 2 x extension bars (125mm, 250mm)
- 11 x sockets (10mm, 11mm, 12mm, 13mm, 14mm, 17mm, 22mm, 24mm, 27mm, 32mm)
- 3 x hex sockets (5mm, 6mm, 8mm)
- 1 x 370mm torque wrench



14 Pieces



18 Pieces

| Number of pieces | Order Code |
|------------------|--------------------------|
| 14 | KEN-534
-2251K |
| 18 | -2255K |



Committed to safety. Committed to change.

Halo is our commitment to keeping your people safe. Every one of them.

We've developed a safety range designed to meet the needs of a modern diverse workforce. Protective, well-fitting and comfortable whatever the size, shape or gender of the wearer. All our products are certified to comply with the latest standards. But most importantly, Halo places the needs of your people at the centre.

Because everyone deserves to be protected.





Cromwell[®]

Famous for



HAND TOOLS



CUTTING TOOLS



AIR & POWER TOOLS



ABRASIVES

Cromwell Exclusive Brands

KENNEDY[®]

SENATOR[®]
QUALITY TOOLING

KOBE[®]

SHERWOOD[®]
QUALITY CUTTING TOOLS

YORK[®]
ABRASIVES

Halo[®]

and many more

Authorized Channel Partners



CHENNAI

Address:- Old No 158 New No. 325, Linghi Chetty Street, Channi-600001.
Branch (Sriperumbudur):- 29, Panjalpettu Village, Chennai Bangalore Highway, Sriperumbudur, Tamilnadu-602105
Email:- info@madrastools.net
Phone:- +91-98401-79451, +91- 80158-44478
GST No:- 33AAAPN9529P1Z6
MSME:- UDYAM-TN-02-0054132

PUNE

Address:- Shop No 2, 1045, Vishwashanti Building, Raviwar Peth, Pune - 411002
Branch (Talegaon):- Shop No: 1,2,3,4 Block Sector, Katavi Distric, Talegaon Dabhade, Pune - 450506
Email:- madrastoolspune@gmail.com
Phone:- +91-84464-47152, +91- 98404-22553
GST No:- 27EVSPM6059N1ZG
MSME:- UDYAM-MH-26-0345577